

Metallic Bopp (PET liner)

Spec# B7764

Description

A topcoated, biaxially-oriented polypropylene film with a mirror-like metallic appearance. The material offers excellent diecutting and dispensing characteristics and is suitable for high-speed converting.

Printable by web screen, UV letterpress and flexographic printing.

Caliper/Thickness 2 mil / 0.0020 inches $\pm 10\%$

Liner

A durable 1.2 mil polyester liner designed for roll-to-roll, high-speed diecutting and dispensing applications.

Adhesive

Fasson® S7000ER is a clear, general-purpose permanent acrylic adhesive designed for strong adhesion to low surface-energy substrates. It offers excellent wet-out characteristics, water-whitening resistance and good short-term repositionability.

Performance Data

Min. Application Temperature: +25°F (-4°C)

Service Temperature Range: -40°F to +175°F
(subject to facestock limitations)

Adhesive Performance

Suitable for rigid and squeezable containers and designed to provide lasting adhesion on low surface-energy substrates.

Recycling

S7000ER features AD CleanFlake™ Technology to support the recycling of PET and HDPE plastic bottles and containers. For metallized film labels, constructions up to 30 square inches can be recognized in existing recycling streams. Larger labels require application-specific testing.

FDA Compliance

Fasson® S7000ER complies with FDA 21 CFR 175.105 for indirect food contact.

Printing Note

Use caution when printing inks or varnishes to the edge of the label. High-shrinkage coatings may cause the label to lift from the liner or substrate. Testing prior to final ink selection is recommended.

Optimal Storage Conditions

Ideally store at 72°F and 50% RH.



QUESTIONS? WE'RE HERE TO HELP!



866-295-4822



info@labelmakers.com



The color of the material shown may vary. Therefore, we recommend that you order our free online sample book at labelmakers.com/sample-book/ to get a better understanding of the effects and different textures.

Order free of charge:



SAMPLE BOOK